



Subcategories Grid/List

User Guide

Installation Instructions

If you purchased extension on our site then unpack .zip file inside your Magento root.

If you purchased extension on Magento Marketplace then unpack .zip file inside **app/code/Apptrian/Subcategories/** directory.

- Run following commands on Magento root directory:

```
php bin/magento maintenance:enable
php bin/magento module:enable --clear-static-content Apptrian_Subcategories
php bin/magento setup:upgrade
php bin/magento cache:flush
php bin/magento setup:static-content:deploy
php bin/magento maintenance:disable
php bin/magento cache:flush
```

If you do not know how to install an extension or you wish a professional to do it for you, we offer additional [Installation](#) service for a small fee.

Configuration

Our extension works out of the box. If you want to configure it differently log to your Magento Admin and go to:

Stores > Configuration > Apptrian Extensions > Subcategories Grid/List

There are more than several options for customization. They are all self-explanatory and have comments and tooltips.

After changing options make sure you refresh your Magento cache.

Customization Instructions

If you want to style Subcategories Grid/List further, copy

```
./app/code/Apptrian/Subcategories/view/frontend/web/css/apptrian_subcategories.css
```

to

```
./app/design/frontend/YourVendor/your_theme/Apptrian_Subcategories/web/css/apptrian_subcategories.css
```

and add your CSS styles.

Read comments in the CSS file and you will be able to make most of the changes in a very succinct way.

If you do not know how to style with CSS or you wish a professional to do it for you, we offer additional CSS Custom Style service for a small fee.

To add subcategories block inside any CMS page content or CMS block use following code:

Example with few options:

```
{{block class="Apptrian\\Subcategories\\Block\\GridList" name="apptrian.subcategories.block"
template="Apptrian_Subcategories::grid_list.phtml" encoded_options="[\`layout\`:\'grid\`,
\`single_link\`:\'0\`"]}}
```

Example with all options:

```
{{block class="Apptrian\\Subcategories\\Block\\GridList" name="apptrian.subcategories.block"
template="Apptrian_Subcategories::grid_list.phtml" encoded_options="[\`layout\`:\'list\`,
\`single_link\`:\'0\`, \`sort_attribute\`:\'name\`, \`sort_direction\`:\'desc\`, \`heading\`:\'Subcats\`,
\`sort_order\`:\'0,1\`, \`image\`:\'image\`, \`name\`:\'name\`, \`description\`:\'meta_description\`,
\`category_ids\`:\'20,3,5\`, \`mode\`:\'specific\`"]}}
```

You can change "encoded_options" attribute to your wishes. (You do not need to type all of them, just the ones you want to override.) Watch out for `category_ids`:20,3,5` the 20,3,5 are category IDs so you need to change these to categories you want to show.

Below is an example on how to add subcategories block to any location via the .xml file. Please read the comments.

```
<?xml version="1.0"?>
<!--
/**
 * @category Apptrian
 * @package Apptrian_Subcategories
 * @author Apptrian
 * @copyright Copyright (c) Apptrian (http://www.apptrian.com)
 * @license http://www.apptrian.com/license Proprietary Software License EULA
 */
-->
<page xmlns:xsi="http://www.w3.org/2001/XMLSchema-instance"
xsi:noNamespaceSchemaLocation="urn:magento:framework:View/Layout/etc/page_configuration.xsd">
    <body>
        <referenceContainer name="content">
            <block class="Apptrian\\Subcategories\\Block\\GridList"
                name="apptrian.subcategories.home.page.after"
                template="Apptrian_Subcategories::grid_list.phtml"
                after="--"
                ifconfig="apptrian_subcategories/home_page/show_after_content" />
            <block class="Apptrian\\Subcategories\\Block\\GridList"
                name="apptrian.subcategories.home.page.before"
                template="Apptrian_Subcategories::grid_list.phtml"
                before="--"
                ifconfig="apptrian_subcategories/home_page/show_before_content" />
        </referenceContainer>

        <!-- Below is an example of how to add subcategories block to any other block.
        You might want to add subcategories options yourself via argument. (You can add
        only options (items) you want to override no need to type all of them.)
        You can also add subcategories block to some other non-container block but then
        you need to call subcategories block in the parent block .phtml file with:
        $this->getChildHtml('apptrian.subcategories.home.page.custom');
        Be aware that name attribute of the subcategories block you add
        should be unique and not clash with the above predefined name attributes. -->

        <!--
```

```

<referenceContainer name="footer">
  <block class="Apptrian\Subcategories\Block\GridList"
    name="apptrian.subcategories.home.page.custom"
    template="Apptrian_Subcategories::grid_list.phtml"
    after="-">
    <arguments>
      <argument name="config_options" translate="false" xsi:type="array">
        <item name="layout" xsi:type="string">grid</item>
        <item name="single_link" xsi:type="string">0</item>
        <item name="sort_attribute" xsi:type="string">position</item>
        <item name="sort_direction" xsi:type="string">asc</item>
        <item name="heading" xsi:type="string">Subcategories</item>
        <item name="sort_order" xsi:type="string">0,1,2</item>
        <item name="image" xsi:type="string">image</item>
        <item name="name" xsi:type="string">name</item>
        <item name="description" xsi:type="string">meta_description</item>
        <item name="category_ids" xsi:type="string"></item>
        <item name="mode" xsi:type="string">specific</item>
        <item name="exclude_ids" xsi:type="string"></item>
      </argument>
    </arguments>
  </block>
</referenceContainer>
-->

</body>
</page>

```

In XML layouts for category pages, if you want to have special category page functionality, the name attribute of the block must start with `apptrian.subcategories.category.page` but should be unique so proper name attribute for the block should be something like:

`apptrian.subcategories.category.page.custom`

FAQ

Q: How to add subcategories block inside CMS page content or CMS block?

A: To add subcategories block inside any CMS page content or CMS block use following code:

```

{{block class="Apptrian\\Subcategories\\Block\\GridList" name="apptrian.subcategories.block"
template="Apptrian_Subcategories::grid_list.phtml" encoded_options="['layout':`grid`,
`single_link`:`0`]"}}

```

Attribute "encoded_options" can be used to override any option that exists in our extension. In the above example, only two options are shown. For more information, please check our User Guide.

Q: Is it possible to turn off subcategories description text?

A: Yes it is. In our extension configuration for option "Sort Order" instead of "0,1,2" type "0,1" (without double quotes). Do not forget to Refresh your Magento Cache.

Q: Why after uploading category image I still get placeholder image?

A: Category model in Magento 2 has only one attribute for image "Category Image". In our extension config for option "For Image Use" you need to select "Image". We left the option "Thumbnail" just in case Magento team brings back category "Thumbnail" in some future version of Magento.

Q: Why after uploading category image for a specific language (store view) I still get placeholder image?

A: You must upload an image to the default scope (All Store Views) **First** and then if you need an image to be different for a specific language (store view) you upload a different image for that particular language (store view).